$65 \frac{3}{4} \times 42 \times 24$  inches





# FEATURES ~

- Deep, ergonomic bathing well
- Suitable for undermount installation
- Pre-leveled support base
- Slip resistant floor
- Premium cast acrylic surface
- Limited lifetime warranty



# **AVAILABLE SYSTEMS**

# AIR BATH



- Perimeter air injectors
- Variable speed heated-air blower
- Automated purge and dry system
- Electronic control with wave and pulse features
- LED Chromatherapy

# HOTSOAK



- 2 low-profile circulation portals
- 1.5 kW inline maintenance heater
- Ultra-quiet low flow circulation pump
- Electronic one-touch on/off control
- Heat-bent rigid PVC piping

# DRIFTBATH 📚



- Up to 70 water portals
- Quiet, energy-efficient .75 hp pump with integrated heat-transfer
- Electronic control
- 4 high-intensity LED Chromatherapy
- Available in White or Biscuit




# Deck Width 3 1/2 Keypad 65° Deck Width 3 1/2 65° 3/4"

# SoCo 6642

Formerly Serenity 36

 $65 \frac{3}{4} \times 42 \times 24$  inches

Note: Drop-in Serenity models feature a pre-leveled support base.



FEATURES Dimensional Tolerance ± 3/8". Dimensions needed for site preparation should be measured from the unit. Manufacturer assumes no responsibility for preparatory work.

					, , , , , ,		
Type and Model #	Material	System	Powered By	Heater	Controls	Drain	Pkg. Wt. lbs
Soaker #W36AIR6642TO	Cast Acrylic	=	-	-	=	Universal	158
HotSoak #W36AIR6642HS	Cast Acrylic	Water circulation	Pump	1.5 kW Inline maintenance	Electronic	Universal	188
Air Bath #W36AIR6642	Cast Acrylic	Air injection	Variable speed blower	Integrated	Electronic	Universal	188
DriftBath #W36AIR6642DB	Cast Acrylic	Water circulation	Pump	Integrated	Electronic	Universal	199

## DIMENSIONS inches

Width	Depth	Height	Skirt
Inches	Inches	Inches	Height
65 3⁄4	42	24	-

# PLUMBING DIMENSIONS inches

A	В	<b>Drain</b> Diameter / Clearance		
3	10 1/2	2 /13/4		

### NOTES:

1) Where applicable, utilize cut-out templates packed with unit for deck cutouts.

- 2)  $16 \times 16$  minimum access required at pump/blower location(s).
- 3) For Low Profile Deck, framing height will need to be increased by an additional  $1^{\prime\prime}$ .
- 4) If a (3T) tiling flange is selected, then the keypad is located opposite of the flange.

## SUMP DATA inches

Capacity to Overflow	Min. Operating Capacity	WIDTH @ centerline		DEPTH @	DEPTH @ centerline	
gal	gal	Тор	Bottom	Тор	Bottom	
115	-	56 <b>¾</b>	45 <b>¾</b>	34	29 ½	

# ELECTRICAL DATA

Component	Specification	Requirement		
Heated Blower (Air Bath)	10.5 AMP; 120V	15 AMP; 120V, separate circuit; Class A GFCI		
Pump (HotSoak)	1/15 HP; 1.3 AMP; 120V	20 AMP; 120V, separate circuit;		
Heater (HotSoak)	1.5 kW; 12 AMP; 120V	Class A GFCI		
Pump (DriftBath)	3/4 HP; 8.8 AMP; 120V	15 AMP; 120V, separate circuit; Class A GFCI		

Each Serenity air bath is equipped with an air heating system to raise the temperature of the air entering the bath. This air temperature will be lower than the bathing temperature of the water, but will help reduce rapid decrease in water temperature. In addition, the air coming from the air jets will feel cool against the skin. This system does not heat the water.

Rev. 04.05.21